

power generation

EnergenTM is more than just an additive. All additives are soluble into the fuel however few truly become part of the fuel. EnergenTM is different in that all of its components have been infused into the fuel that they are treating thus becoming part of the fuel and combusting with the fuel for a more complete burn. This is what we call a "Fuel Conditioner".


Energen™, A Proven Fuel Saver & Anti-pollutant, A Fully Tested Fuel Oil Conditioner, by being part of the fuel allows for it to;

- Greatly reduce fuel consumption by delivering more energy from less fuel
- Stabilises the fuel, vastly improving the fuel oils compatibility
- Dissolves sludge formation in tanks and lines, greatly improving the fuels reliability
- Combustion Improver, via better atomisation and vaporisation resulting in brighter active flames
- Efficiency Improver, greatly reducing soot build-up on boiler heat transfer surfaces and lowers stack temperature
- Cleans the environment by inhibiting particulates, black smoke and polluting stack discharges

CONSERVES FUEL OIL AND CLEANS THE MECHANICAL ENVIRONMENT resulting in less fuel used and a cleaner environment.

EnergenTM FuelOil (HFO, IFO & LFO), Heating Oil and No. 2-6 Diesel Conditioner, breaks down the hydrocarbon chains of the fuel. This greatly improves the vaporisation and atomisation of the fuel. As a result of this, there is greatly Improved positive combustion with more heat output, and greatly increased Steam Production Ratio of more Steam Produced per Litre of FuelOil / No. 2-6 Diesel burned.





- directly to the fuel tank or bulk fuel storage tank
- allow up to 24 hours blend time



P.O. Box 222, Caulfield South, VIC 3162 Australia

A.B.N. 12 618 916 813

Contact: +61 (0)4 2255-1112 info@energen.co



Liquid Fuel Engineering